

### Technical Specifications:

**Tube:** High-grade synthetic rubber for petroleum and oil resistance

**Reinforcement:** High-strength textile cord with embedded steel wire helix for superior suction performance

**Cover:** Abrasion and weather-resistant synthetic rubber

**Temperature Range:** -20°C to +80°C

**Color:** Black with markings



### Description:

Fuel/Oil Suction Hoses are designed for efficient and reliable transfer of petroleum products and oil-based fluids in various industrial applications. These hoses provide durability, flexibility, and resistance to external elements.

Size	Inner Diameter (ID)	Length	Working Pressure (WP)
1 1/4"	45mm	30m	WP33
1 1/2"	51mm	30m	WP29
2"	64mm	30m	WP22
2 1/2"	77mm	30m	WP18

### Features:

- ★ Excellent resistance to oil and petroleum products
- ★ High suction and discharge capacity
- ★ Robust construction with a steel wire helix for flexibility and crush resistance
- ★ Suitable for high-pressure applications
- ★ Durable outer cover for abrasion and weather resistance

### Applications:

- ★ Oil and fuel transfer in refineries
- ★ Industrial fuel handling
- ★ Suction and discharge of petroleum-based fluids
- ★ Marine and dockside operations
- ★ Fuel delivery trucks