PVC REINFORCED HOSE

PRODUCT DATA SHEET

Technical Specifications:

Material: PVC (Polyvinyl Chloride) with Reinforced Polyester Yarn

Temperature Range: -10°C to 60°C (14°F to 140°F)

Brand: Kuwes



Description:

The PVC Reinforced Hose is a versatile and durable tubing solution designed for various fluid transfer applications. Constructed from high-quality PVC material with reinforced polyester yarn, this hose offers excellent strength, flexibility, and resistance to abrasion, kinking, and crushing. Suitable for use in a wide range of industries, including agriculture, construction, landscaping, and automotive.

Features:

- *Durable Construction: Made from high-quality PVC material reinforced with polyester yarn for enhanced strength and durability.
- *Flexibility: The hose remains flexible even in cold temperatures, allowing for easy handling a nd installation in various environments.
- *Resistance to Abrasion: Designed to withstand abrasion and wear, ensuring long-lasting performance in demanding applications.
- *Kink and Crush Resistance: Resistant to kinking and crushing, maintaining consistent flow and performance under pressure.
- *Chemical Compatibility: Compatible with a wide range of chemicals, acids, and alkalis, making it suitable for diverse fluid transfer applications.
- *UV Resistance: Exhibits excellent resistance to UV radiation, ensuring stability and longevity in outdoor environments.
- *Temperature Range: Suitable for use in temperatures ranging from
 - -10°C to 60°C (14°F to 140°F), making it versatile for both hot and cold applications.
- *Versatile Use: Ideal for use in agriculture, construction, landscaping, irrigation, drainage, and other fluid transfer applications.

Applications:

- *Agriculture
- *Construction
- *Landscaping
- *Irrigation
- *Drainage
- *Automotive
- *Fluid Transfer

